TECHNICAL DATA SHEET

PSS Multiaxis Rotative Support for PCBs up to 13 x 13 cm / 5 x 5 in

Save time and optimize workflow.
PSS enables quick, precise PCB position changes, **ensuring proper positioning for repetitive soldering tasks.**
This support adapts perfectly to any type of PCB up to 130 x 130 mm / 5 x 5 in by means of its many adjustable elements.
Features:

- **Horizontal-axis swivel**

Turn the PCB holder 180º upside down and choose among 4 different angular positions 25º, 35º, 45º and 55º.

- **Vertical-axis swivel**

Allows positioning the PCB at any angle. It can be rotated in horizontal and inclined position.

- It provides **3 heights.**

When combined with **PHSE Preheater** its built-in slots ensure precise board-preheater alignment to always heat the same area.
Check out **more information** about features of PSS.



REFERENCES

PSS-A

PRODUCT COMPOSITION

1 - Instruction Manual
1 - PSS Multiaxis Rotative Support for PCBs up to 13 x 13 cm / 5 x 5 in

SPECIFICATIONS

ESD safe connector

Max. dimensions

Low position	267 x 259 x 75 mm 10.5 x 10.2 x 3 in
High position	267 x 259 x 96 mm 10.5 x 10.2 x 3.8 in
Max. Diameter (Rotated Position)	300 mm / 11.81 in
Max. Height (Flip)	300 mm / 11.81 in
Max. PCB Dimensions	13 x 13 cm / 5 x 5 in

TECHNICAL DATA SHEET

PSS Multiaxis Rotative Support for PCBs up to 13 x 13 cm / 5 x 5 in

WEIGHT AND DIMENSIONS

Control Unit	235 x 245 x 80 mm / 2.50 kg 9.25 x 9.65 x 3.15 in / 5.51 lb
Package	368 x 368 x 125 mm / 3.47 kg 14.49 x 14.49 x 4.92 in / 7.65 lb